

# Ventolite Blinds CC *Perfect Sun Control*

## 50mm Fauxwood Venetian Blind

### Specifications

Slat Width	50mm - Tolerance 0.3mm
Slat Thickness	3.2mm - Tolerance 0.3mm
Camber	Maximum 2mm on 1500mm
Bow	Maximum 5mm on 1500mm
Width of Headrail	57mm
Height of Headrail	51mm
Width of Bottomrail	51mm
Height of Bottomrail	16mm
Height of Valance	63.5mm
Maximum Recommended Width	1650mm
Maximum Recommended Drop	2200mm
Maximum Recommended Area	3m <sup>2</sup>
Minimum Width	350mm, Both Tilt and Lift Cord on One Side
Maximum Ladder Lace Spacing From End To First ladder	130mm
Maximum Ladder Lace Spacing Between Ladders	350mm
Slat, Bottomrail & Pelmet Material	Polystyrene
Headrail	Colour Co-ordinated Cold Rolled Steel, Zinc Chromate Primed
Cord Lock Mechanism	Moulded Plastic
Internal Components	Moulded Plastic
Tassel & Tape Buttons	Colour Co-ordinated Wood For Tassel & Colour Co-ordinated Plastic For Tape Button
Tilter Mechanism	Metal
Fixing Brackets	Universal Electroplated Zinc Metal
Tilt Shaft	Steel
Cords	Colour Co-ordinated 2mm Polyester Yarn
Ladder Lace	Colour Co-ordinated 53mm x 44mm x 2mm Polyester Yarn
Edges	Rounded Sides, Ends Straight Cut
Temperature	Up To 71 Degrees Celcius, Maximum Distortion 2mm

### Approximate Stacking Height

	Height			
	1000mm	1500mm	2000mm	2500mm
Stack	135mm	165mm	195mm	225mm

**Contact Details:** Tel: 031 579 2670  
 Fax: 031 579 2680  
 Email: [orders@ventolite.co.za](mailto:orders@ventolite.co.za)  
 Web: [www.ventolite.co.za](http://www.ventolite.co.za)

**Address:** Ventolite Blinds CC  
 Unit 19 Springriver Park  
 48 Ebonyfield Avenue  
 Springfield Park  
 Durban